



Bitumen Flashing Tape

Product Code: S820

Warranty:

Pomona S820 Bitumen Waterproof Flashing Tape is designed to withstand normal New Zealand weather conditions in external flashing situations. If applied correctly and maintained in an approved way it will provide watertight seals for a minimum period of 15 years.

Surface Preparation:

Surfaces need to be sealed and must be completely dry and clean. Surfaces should be tested for bonding compatibility with Bitumen adhesive.

Contamination from previous sealants and coatings must be removed completely. Surfaces must be wiped with approved cleaners that contain no residual contamination (e.g. Turpentine, white spirits etc.). Acetone and IPA are suitable cleaners. Alternative cleaners may be used with the written approval of Pomona Group Limited.

Application Method:

There must be sufficient coverage of any joint - a minimum of 50mm is required each side of a flashing joint and this may need to increase in exposed coastal situations.

S820 can only be applied above 10°C and preferably temperatures of 20°C to 30°C to achieve good contact and instant bond.

A wooden roller should be used to press the tape down evenly onto the roofing substrate. A flat even surface of tape without wrinkles is required.

Finishing:

S820 is compatible with most paint systems. A top coat of roof paint will provide further protection from UV degradation.

The information provided above is based on our experience and tape industry knowledge. It is given in goodwill but is not intended as a guarantee or warranty. All end users should ensure for themselves that the product is suitable for their own application before using.

Pomona Group Limited

PO Box 21806 | Henderson | Auckland 0650

P: 0800 POMONA E: sales@pomona.co.nz

100% New Zealand Owned and Operated

www.pomona.co.nz