

HDPE Automotive Drape Film



HDPE Film

PRODUCT COMPOSITION

SPECIFICATIONS	
Code	S6650
Description	11um HDPE Masking Film
Features and Benefits	Suitable for water and solvent-based paints Easy to remove
Areas of Use	Professional automotive painting applications
Industries	Automotive / Marine Trade
Colour	Clear
Sizes Available	120m x 5m
Slitting Options	N/A

PHYSICAL PROPERTIES	
Backing (Liner)	HDPE Film
Type	Corona Treated
Elongation at Break (%)	150
Temperature Resistance (°C)	60
Total Thickness (mm)	0.015 (15 Microns)

TAPE STORAGE

Ideally, store tape between 15°C and 25°C with a maximum relative humidity of 65%. Always store away from heat sources, avoiding exposure to light and if possible keep in the original packaging.

OTHER INFORMATION

All test methods are based on ASTM standards and Pomona's standardised test methods. The information provided above is based on our experience and tape industry knowledge. It is given in goodwill but is not a guarantee or a warranty. All end-users should ensure for themselves that the product is suitable for their particular application before using.

NB: Peak Force Test: based on ASTM 3759/D ASTM 3759/M and Pomona® test methods,
Peel Test: based on ASTM D3330 and Pomona® test methods.

Pomona products are registered and under trademark of PGL and sold exclusively through selected distributors. For further information on Pomona please email sales@pglgroup.co.nz, phone 0800 766 662 or contact your distributor.