


Double Sided Washi Masking Tape



PRODUCT COMPOSITION

SPECIFICATIONS	
Code	S210
Description	Genuine Japanese Washi Paper with Acrylic Adhesive
Features and Benefits	Can be used to hang masking drape films for big wall surface masking Ideal for hanging children's artwork and posters Holding rugs in position on wooden floors 30 day clean removal on most surfaces Can be used to hold stencils in place for creative decorating projects Suitable for all types of surfaces
Areas of Use	Suitable for all types of surfaces
Industries	Decorative / Trade / Retail / Education / Craft
Colour	Yellow
Sizes Available	18mm x 33m (48 Rolls / Carton) 24mm x 33m (36 Rolls / Carton) 36mm x 33m (24 Rolls / Carton) 48mm x 33m (18 Rolls / Carton)
Slitting Options	Available on request

PHYSICAL PROPERTIES	
Backing (Liner)	Genuine Japanese Washi Paper
Adhesive Type	Water Base Acrylic
Initial Tack	10 - 14
Adhesion to Steel Plate (N/25mm)	2.0N - 3.5N
MD Elongation at Break (%)	5.8 - 6.5
MD Tensile Strength	46N - 50N
UV Light Resistance	30 Days
Temperature Resistance (°C)	100
Total Thickness (mm)	120 (±10µm)

The figures above are based off average results from multiple tests, results may vary + or - 5%

100% New Zealand Owned & Operated

CONDITIONS OF USE

For best results apply self-adhesive labelopes between 15°C and 25°C in a dry environment. Application surfaces must be dry and free from dust and particles. Do not apply on surfaces treated or contaminated by anti-adhesives. Avoid contact with surfaces containing plasticizers or other chemical agents not compatible with the tape. Care must be taken regarding removability without residue and working conditions of the self-adhesive labelopes.

TAPE STORAGE

Ideally, store labelopes between 15°C and 25°C with a maximum relative humidity of 65%. Always store away from heat sources, avoiding exposure to light and if possible keep in the original packaging. When temperatures are lower than 15°C, it is highly recommended to recondition the adhesive labelope to the average temperature range (15°C to 25°C) before use.

TAPE SHELF LIFE

Self-adhesive labelopes technical features are generally not permanent but remain at their best for approximately 12 months, if stored according to suggested conditions and by avoiding extreme environmental conditions such as quick and sudden temperature changes, exposure to UV light and high levels of humidity.

OTHER INFORMATION

All test methods are based on ASTM standards and Pomona's standardised test methods. The information provided above is based on our experience and tape industry knowledge. It is given in goodwill but is not a guarantee or a warranty. All end-users should ensure for themselves that the product is suitable for their particular application before using.

NB: Peak Force Test: based on ASTM 3759/D ASTM 3759/M and Pomona® test methods,
Peel Test: based on ASTM D3330 and Pomona® test methods.

Pomona products are registered and under trademark of PGL and sold exclusively through selected distributors. For further information on Pomona please email sales@pglgroup.co.nz, phone 0800 766 662 or contact your distributor.